



Holtz Industries, Inc. | 200 South Terrace Court | Newark, OH 43055

TF: 1-800-535-0104 | Web: [www.holtzindustries.com](http://www.holtzindustries.com)

TM - Models

## ABOVE FRAME (AF-SERIES)

### CABLE HOISTS

#### MODELS: AFCA-TM-22 & -24

**(AFCA-TM) – California Trough Mount** The trough section atop the hoist frame can be manufactured to specific widths and with variations to the tail sections. AFCA-TM hoists can haul a variety of containers with various understructure layouts. Although designed for the West Coast market, these models can be easily adapted for applications in other areas around the country.





## Standard Features


- Inside air controls mounted in our ergonomic Power Tower featuring Plug And Play™ wiring
- Outside controls mounted on driver's side
- Air assist auto folding ICC bumper
- Pintle ready rear aprons featuring a split bumper with LED lighting
- 10" wide troughs with flared tails
- All pivot joints & sheave blocks are easily accessed for service and grease
- 3 micron return filtration inside of steel tank with dual sight/temperature gauge
- Lifetime warranty on hoist frame, 2 year limited hydraulic system warranty
- Customized engineering layouts ensure the exact fit for each customer
- Back up alarm and hoist up alarm with signal light

FEATURE	
Hoist main frame	10" x 4" x 1/2" – A500 Grade C structural tubing
Hoist sub frame	4" x 4" x 1/4" – A500 Grade C structural tubing
Hydraulic pump	Direct mount gear type, 37 1/2 gpm @ 1,500 rpm
Operating pressure	3,200 PSI
Hydraulic valve	2 spool / 45 gpm with safety bypass
Oil reservoir	47 gallon BTC with 3 micron return filtration system
Lift cylinders	(2) DA – dual acting rod type
Hinge shaft	2 1/2" solid steel
Winch cylinder	(1) DA – dual acting rod type
Cable end	Oval eye
Cable sheaves	10" OD" grease grooved w/ bronze bushings
Cable anchors	Wedge and ferrule
Front stop	(2) moveable steel blocks (various styles offered)
Front hold downs	Heavy duty nylon ratchet straps
Rear hold downs	Heavy duty nylon ratchet straps


\* Factory mount models



Behind the cab, steel tank with 3 micron return filtration (pictured at left)



HD nylon ratchet container hold downs



Inside air controls center mounted in ergonomic Power Tower featuring Plug And Play™ wiring. (Top) traditional cab, (bottom) cab over.



Huck bolted to chassis frames\*



Air Assist Auto Folding ICC Bumper



HD rear apron pintle ready with split bumper and LED lighting





## Available Options

- Steel, aluminum and poly fenders
- Pioneer tarping systems
- Trough width and flared tail variations
- Auxiliary stops and hold down systems
- Auxiliary hydraulic hook-ups/wet kits
- Hard plumbing
- Lift axles
- Tires and rims (steel, aluminum)
- Pintle hook and reese style hitch assemblies
- Speed limiting parameters for hoist up ground speed
- Scale systems
- Available in traditional U-Series models
- Special models per customer request
- Cable end types



Toolbox styles and sizes.



Pioneer tarping systems.



Trough widths (10" most common) and Tail flaring styles available.



3 styles of moveable stops.

**AFCA-TM-24** shown with Pioneer Rack 'n Pinion™, safety hi-vis lighting and move-able Standard Shoe front stop options.



**AFCA-TM**